



DOG-208FA Industrial Dissolved Oxygen Electrode

DOG-208FA high temperature dissolved oxygen electrode, which is specially designed to be resistant to 130 degrees steam sterilization, the pressure auto-balance high temperature dissolved oxygen electrode, for liquids or gases dissolved oxygen measurement, the electrode is most suitable for small microbial culture reactor dissolved oxygen levels on line. Can also be used for environmental monitoring, waste water treatment and aquaculture on-line measurement dissolved oxygen levels.

Dissolved oxygen electrode characteristics

1. DOG-208FA high temperature fermentation dissolved oxygen electrode applicable for Polarographic Principle
2. With imported breathable membrane heads
3. Steel gauze electrode membrane and silicone rubber
4. Endure high temperature, No deformation characteristics

Technical Indexes

1. Electrode body material: SS316L
2. Permeable membrane: fluorine plastic, silicone, stainless steel wire mesh composite membrane.
3. Cathode: platinum wire
4. Anode: silver
5. Electrodes built-in temperature sensor: PT1000
6. The response current in the air: About 60nA
7. The response current in a nitrogen atmosphere: less than one percent response current of response in air.
8. Electrode response time: about 60 seconds (up 95% response)
9. Electrode Response Stability: a constant oxygen partial pressure at a constant temperature environment, response current drift less than 3% per week
10. Liquid mixing flow to the electrode response: 3% or less (in water at room temperature)
11. Electrode Response Temperature Coefficient: 3% (greenhouse)
12. Insert the electrode diameter: 12 mm, 19 mm, 25 mm optional
13. Electrode insertion length: 80, 150, 200, 250, 300 mm

